




Radio Assisted Toilet Alarm Kit

Wireless ATA Ceiling Pull Cord

- Programmable ID's - 1 - 240 (Programmer required or can be programmed at factory)
- Programmable House code - 0 - 9 (Programmer required or can be programmed at factory)
- Frequency - 433.920 Mhz
- Band - FM
- Transmitter power - 10mw
- Radio standards - EN 300 220-3
- EMC Standards - EN301 489-3
- Transmission format - Fast format Trinary
- Power - MN1604 Alkaline Battery (9 volt)
- Battery Life - 1 - 2 years
- Battery Low - Transmitted to Over Door Lamp/Sounder or display panel if installed (Sounder on Over Door Lamp beeps twice every minute)
- Transmit a call - Pull cord single or multiple times
- Cancel a call - Pull cord twice at reasonable speed. (Can only be done after call placed)
- Maximum range - 30 - 50 metres internal & 100 -150 metres open ground
- Boosters - Booster available as separate product



Wireless ATA Over Door Lamp - Sounder

- Programmable ID's - 1 - 32 programmable slots.
Can program slots with numbers between 1 - 240
Can be programmed to receive 32 different calling device at any one time.
(Programmer required or can be programmed at factory)
- Programmable House code - 0 - 9 (Programmer required or can be programmed at factory)
- Frequency - 433.920 Mhz
- Band - FM
- Receiver sensitivity - 108dBm
- Radio standards - EN 300 220-3
- EMC Standards - EN301 489-3
- Receive data format - Fast format Trinary
- Power - Lithium Battery 3.6 volt AA cell
- Battery Life - 1 year
- Battery Low - Sounder beeps once every minute
- Sounder - Peizo 60 - 65 db @ 1 meter
- Lamp - Red lamp - Flashes rapidly when alarm activated
- Maximum range - 30 - 50 metres internal & 100 - 150 metres open ground

Technical Alarm Systems Limited

Unit 2, Muira Industrial Estate, William Street, Southampton, SO14 5QH

Tel: 0845 3899449 Fax: 0845 3891716 email: sales@technicalalarmsystems.co.uk